



KEY FEATURES

- "Super High Impact" Panel for Highly Abused Spaces
- Decorative Fabric Facings from Guilford of Maine as well as Designer Selections from Maharam, Carnegie, DesignTex, Knoll, & More!
- Custom-Printed Digital Imaging Available
- Standard and Custom Sizes & Shapes Available
- Easy to Install with Fully-Concealed Mounting Hardware Included
- Indoor Air Quality (IAQ) & Low VOC Meets GREENGUARD Children & Schools Certification and California Title 24
- Low VOC Emissions per CDPH Standard Method

TECHNICAL FEATURES

- Core: 6-7 PCF Fiberglass
- Core Facing: 1/16" Impact Resistant & Acoustically Transparent Perforated Copolymer Sheet
- **Thickness:** 1-1/16", 1-9/16", 2-1/16", 3-1/16"
- Sizes: Any Size Up to 48" x 120"
- Special Sizes & Shapes: Available Upon Request
- Edge Profile: Square, Bevel
- Fabric: Decorative Fabric Facings, Designer Selection or C.O.M. Standard: Guilford FR701-2100 Series / Premium: Guilford Anchorage 2335
- Fasteners: Z-Clip, Z-Bar, Impaling, Hook & Loop
- Dimensional Tolerance: +/- 1/16" (.0625")
- Fire Performance: Class 1/A, UL 723 / ASTM E84

ACOUSTICAL DATA

Acoustical Performance - Absorption Coefficients								
Frequency (Hz)		125	250	500	1K	2K	4K	NRC
ATPE 1.1	1 -1/16" Panel	0.09	0.38	0.98	1.25	1.19	1.07	0.95
ATPE 1.6	1-9/16" Panel	0.36	0.78	1.13	1.10	1.15	1.39	1.05
ATPE 2.1	2 -1/16" Panel	0.32	0.93	1.18	1.17	1.13	1.05	1.10
ATPE 3.1	3 -1/16" Panel	0.94	1.00	1.14	1.21	1.20	1.47	1.15

LEED CREDITS

- Schools EQ Prerequisite 3 & Credit 9
- MR 4.1 & 4.2
- MR 5.1 & 5.2

- IEQ 4.1 & 4.2
- Innovation in Design (ID)
- Low VOC Emissions per CDPH Std. Method

WARRANTY

AVL Systems' Limited Warranty extends for ONE FULL YEAR from the original date of shipment.

58% TOTAL RECYCLED CONTENT* 31% Pre-Consumer Recycled 27% Post-Consumer Recycled





